

PRESSURE GAUGE



FEATURES

- Stainless Steel Case
- Oil Filled
- Socket Directly Welded to Case
- Protection IP 65
- Aseismatic
- Dual Scale Measuring (psi & kg/cm²)

TECHNICAL FEATURES

- Dial Size: 63mm (2.5")
- Mounting: Back Mounting / Direct Bottom Mounting
- Accuracy: ±1.6% of Full Scale Value
- Ambient Temp: -25 to 65°C
- Process Temp: Max 300°C
- Op Pressure: 75% of Scale Value
- Over Pressure Limit: 130% of Max Scale Value
- Case: AISI 304SS, DIN Type
- Vent Plug & Gasket: EPDM

Model	Dial Size	Mounting	Measuring Range		Connection BSP	Bracket
			psi	kg/cm ²		
PG-B-150	63mm (2.5")	Back	0 - 150	0 - 10.4	¼" Male	Back Hold
PG-B-240	63mm (2.5")	Back	0 - 240	0 - 16.5	¼" Male	Back Hold
PG-B-350	63mm (2.5")	Back	0 - 350	0 - 25	¼" Male	Back Hold
PG-BT-150	63mm (2.5")	Bottom	0 - 150	0 - 10.4	¼" Male	
PG-BT-240	63mm (2.5")	Bottom	0 - 240	0 - 16.5	¼" Male	
PG-BT-350	63mm (2.5")	Bottom	0 - 350	0 - 25	¼" Male	